



SUPPLEMENTAL/ BID BULLETIN NO. 1

IB2024 – 086E
PROCUREMENT OF 2 UNITS PATIENT TRANSPORT VEHICLE

This Supplemental/Bid Bulletin No. 1 is being issued to revise provisions/specifications in the Bidding Documents for a forecited project:

1. Query during Pre-bidding Conference:		
Technical Specifications	Query	Response of the End User Unit
b. 1 piece with at least 2 kg (4 pounds) placed on the driver compartment and with holder mounted on the Patient Transport Vehicle floor	b. 1 piece with at least 2 kg (4 pounds) placed on the driver compartment and with holder mounted on the Patient Transport Vehicle floor (driver/passenger area)	b. 1 piece with at least 2 kg (4 pounds) placed on the driver compartment and with holder mounted on the Patient Transport Vehicle (driver/passenger area) GRANTED
Digital clock with at least 20x50 cm display size. The clock must display Hour: Minute: Second. Battery operated. The clock must be mounted on the Patient Transport Vehicle wall.	4. Digital clock with at least 12x30 cm display size. The clock must display Hour: Minute: Second. Battery operated. The clock must be mounted on the Patient Transport Vehicle wall.	4. Digital clock with at least 12x30 cm display size. The clock must display Hour: Minute: Second. Battery operated. The clock must be mounted on the Patient Transport Vehicle wall. GRANTED
b.1 Free preventive maintenance for the vehicle every 10,000 km up to 30,000km as indicated in the vehicle odometer. The free preventive maintenance shall be comprised of free charge oil, break check-up cleaning, and battery check-up.	b.1 Free preventive maintenance for the vehicle every 10,000 km up to 30,000km as indicated in the vehicle odometer. The free preventive maintenance shall be comprised of free change oil, brake check-up cleaning, and battery check-up.	b.1 Free preventive maintenance for the vehicle every 10,000 km up to 30,000km as indicated in the vehicle odometer. The free preventive maintenance shall be comprised of free change oil, brake check-up cleaning, and battery check-up. GRANTED

Bidders are advised to use the **following attached forms and submit them together with all required documents for the submission of bids on the 24th day of September 2024, 9:00 AM:**

This Supplemental/Bid Bulletin No. 1 shall be integral to the Bidding Documents. All other provisions indicated in the bidding documents not affected by this Supplemental/Bid Bulletin No. 1 shall remain in effect.

For guidance and information of all concerned.

Issued this 16th day of September 2024 in MMCHD

Approved by:


JEREMIAS FRANCIS Y. CHAN, MD
 Licensing Officer V / BAC Chairperson

Republic of the Philippines
Department of Health
Metro Manila Center for Health Development

TECHNICAL SPECIFICATIONS

Item No. 1	PATIENT TRANSPORT VEHICLE	Qty./Unit	2 UNITS
Name of Manufacturer:			Country of Origin
Brand:			Model: (if applicable)
ABC: 4,000,000.00			
PURCHASER'S SPECIFICATION			STATEMENT OF COMPLIANCE
<p>TECHNICAL SPECIFICATIONS:</p> <p>I. VEHICLE SPECIFICATIONS AND REQUIREMENTS</p> <p>1. Vehicle type: Four-wheel passenger van with 4 doors (2 at the front for the driver and passenger, one sliding door or barn door at the right side, and tailgate or barn door at the rear)</p> <p>2. Wheelbase: At least 2800 mm</p> <p>3. Drive type: Rear wheel drive</p> <p>4. Engine size/displacement: 2.5 to 3.0 liters</p> <p>5. Engine Type: 4 cylinders, in-line type, 16 valves, Double Over Head Cam (DOHC)</p> <p>6. Fuel-injector system: Direct injection</p> <p>7. Emission Compliance: Euro 4</p> <p>8. Fuel Type: Diesel</p> <p>9. Fuel tank capacity: at least 65 liters</p> <p>10. Transmission: Manual with at least five (5) speed + one (1) reverse</p> <p>11. Steering: Left hand drive with power-steering system</p> <p>12. Brakes: Ventilated disk on the front and ventilated disk or drum type on the rear. With Anti-lock braking system. With parking brake</p> <p>13. Front suspensions: McPherson Strut or Double Wishbone or Torsion Bar with stabilizer</p> <p>14. Rear suspensions: Rigid axle with leaf spring and double acting shock absorbers</p> <p>15. Wheels: At least 15 inch, aluminum mag wheels or steel wheels with or without full cover. If without full cover, the wheels must be painted with silver color.</p> <p>16. Tires: Radial type and at least 195 mm tire width</p> <p>17. Standard vehicle lamps: Head lamps, tail lamps, stop lamps, signal lamps, license plate lamps, fog lamps and step lamps</p> <p>18. Vehicle body color: White</p> <p>19. Floor Material: Metal with anti-static floor matting. Each entry point of the</p>			

patient compartment must be fitted with a diamond tread plate flooring.

20. Standard dashboard instrumentations: Speedometer, odometer, fuel gauge, digital clock, low battery charge, indicator lamps for parking brake and head light high-beam, engine check, door open.

21. Dashboard Camera: Resolution of at least 1920x1080@30fps, angle of view at least 120 degrees diagonal, at least 2 inch LED display, minimum storage capacity of 64Gb, with loop recording, automatic on/off and night vision recording in low light. The camera must be permanently installed on the dashboard or windshield. The power supply must be from the vehicle battery.

22. Standard driver's cabin accessories: AM/FM radio with speakers, USB connector, front personal lamp for driver and passenger, rear view mirror, sun visor and assist grips for the driver and passenger.

23. Windshield Wipers: With at least two (2) speed intermittent with washer

24. Air conditioning system: Dual type; at the driver's cabin and at the patient compartment with independent controls.

25. Seat belts: 3 point Emergency Locking Retractor (ELR) seatbelts for the driver and front passenger.

26. Airbags: Supplemental Restraint System (SRS) airbags for the driver and for the front seat passenger.

27. Driver and passenger side mirrors: Standard convex type, manual or power adjustment.

28. Vehicle interior trim: Moulded trim. The ceiling must be provided with insulation.

29. Stainless steel plate on the rear bumper to protect the bumper when the Patient Transport Vehicle Stretcher is being loaded to the Patient Transport Vehicle.

30. Set of tools: hydraulic jack, tire wrench, flat and Philips screw drivers, set of pliers, adjustable wrench, early warning device and spare wheel and tire.

II. PATIENT TRANSPORT VEHICLE BODY MARKING

1. Each side of the vehicle body shall have the capitalized word "PATIENT TRANSPORT VEHICLE" not less than 15 cm in height and the letters must be in red color. Other requirements such as font and letter spacing shall be in accordance with Annex D of Administrative Order (AO) No 2020-0011.

2. The rear side of the vehicle shall be marked with a reflectorized and capitalized word "PATIENT TRANSPORT VEHICLE" not less than 15 cm in height. The letters must be in color red. Other requirements such as font and letter spacing shall be in accordance with Annex D of Administrative Order (AO) No 2020-0011.

3. The prescribed DOH logo with a diameter of not less than 36 cm shall be placed on the driver's door and on the front passenger door. Other requirements for the logo shall be in accordance with Annex D of Administrative Order (AO) No 2020-0011.

4. Refer to Annex D Administrative Order (AO) No 2020-0011 for the DOH prescribe Patient Transport Vehicle Body Wrapping

III. PATIENT COMPARTMENT

1. Partition between the driver and patient compartment: Airtight bulkhead made of non-porous material with a transparent and shatter-proof sliding window at least 35 cm x 30 cm.

2. Bench for medical personnel: The Patient Transport Vehicle must be fitted with 3-seater bench permanently mounted on the vehicle floor; one on the head side of the patient and one on the right side of the patient compartment. The bench (seat and backrest) must be made of sturdy aluminum frame and panels coated with white color paint or other lightweight, equivalent strength material such as fiberglass reinforced plastics or plastic laminated. The seat and backrest must be fitted with mattress made of polyurethane foam covered with a washable leatherette material. The construction of the bench must be in such a way that the underneath can be used as a compartment. The bench must have a 2 point seatbelt for each person.

3. Overhead lighting: At least 2 LED white lights with low light option

4. Grab rail: Aluminum or stainless steel grab rail at least 120 cm long, 10 cm depth (maximum) installed on the ceiling right above the stretcher.

5. Intercom system: Intra-vehicle intercom system must be fitted to serve as voice communication between the driver and personnel in the patient compartment.

IV. COMMUNICATION EQUIPMENT

Two (2) pieces cellular phones (one for the Patient Transport Vehicle and one for the hospital/base). The cellular phones must be 4G Network, with Internal Memory of at least 64 GB 4G RAM smartphones. The phones must be provided with sim cards and battery charger.

V. PATIENT TRANSPORT VEHICLE STRETCHER

1. Length: 180 – 197 cm

2. Width: 48 – 55 cm

3. Loading height should match the vehicle floor height

4. Loading capacity: at least 175 kg

5. Materials: Stainless steel, high grade aluminum alloy

6. Head part rising angle: at least 75°

7. Knee part rising angle: at least 15°

8. With collapsible side rails and quick release patient restrain system

9. With durable folding leg mechanism

10. The mattress must be made of high-density polyester fiber foam with a thickness of at least 5 cm and covered with waterproof vinyl material.

11. Wheels: 150 - 200mm diameter, fixed front with locking brakes and auto-directional rear and with 50-55 mm loading carriage wheels

12. Loading rail mounted in the Patient Transport Vehicle with latching system

13. Non-removable DOH logo and the words "For Patient Transport Vehicle

use only” must be marked on the visible part of the equipment

VI. OXYGEN CYLINDER WITH OXYGEN THERAPY SET

1. At least 20pound capacity
2. Must be color green
3. Oxygen therapy set
 - a. Gauge reading: 1,800 psi or higher
 - b. Flowmeter: 0 to 15 li/min
 - c. Humidifier bottle: Hard plastic, capacity: 200ml to 300ml
 - d. Accessories: mouthpiece, tubing, open wrench for installing the therapy set to the cylinder
4. The cylinder must be placed in a holder mounted on the head side of the patient
5. Non-removable DOH logo and the words “For Patient Transport Vehicle use only” must be marked on the visible part of the equipment

VII. OTHER EQUIPMENT AND ACCESSORIES

Note: *The items below (except the IV holder) must be marked with Non-removable DOH logo and the words “For Patient Transport Vehicle use only” on the visible part of the equipment.*

1. Fire extinguishers with rating 2A10BC:
 - a. 1 piece with at least 5 kg (10 pounds) placed on the patient compartment and with holder mounted on the Patient Transport Vehicle floor.
b. 1 piece with at least 2 kg (4 pounds) placed on the driver compartment and with holder mounted on the Patient Transport Vehicle floor (driver/passenger area)
2. Heavy duty LED flashlight with at least 1,000 lumens of brightness. The flashlight battery can be rechargeable or non-rechargeable. For non-rechargeable batteries, an extra set of batteries must be provided.
3. IV holder with at least 2 hooks and mounted on the Patient Transport Vehicle wall head side of the patient.
4. *Digital clock with at least 12x30 cm display size. The clock must display Hour: Minute: Second. Battery operated. The clock must be mounted on the Patient Transport Vehicle wall. GRANTED*
5. *Air purifier with multi-stage air filters (Pre-filter, HEPA, Carbon) and with UV light. The size of air purifier must be appropriate for the Patient Transport Vehicle.*

OTHER DOCUMENTARY REQUIREMENTS TO BE SUBMITTED DURING THE BID OPENING

1. Product brochure(s) or technical data sheet(s) in Hard and Soft copies showing the technical specifications of the following in English language:
 - a. Patient Transport Vehicle showing the vehicle specifications and the

<p>required components in the patient compartment</p> <ul style="list-style-type: none"> b. Patient Transport Vehicle Stretcher c. Oxygen Cylinder with Oxygen Therapy Set <p>2. Notarized Certificate from the manufacturer or local dealer of the vehicle:</p> <ul style="list-style-type: none"> a) That the manufacturer has been manufacturing vehicles with diesel engines for the past twenty-five (25) years. b) That the vehicle is brand new, unused, not a discontinued model and was not subjected to any product recall. 	
<p>Requirements if awarded the Contract</p> <ol style="list-style-type: none"> 1. The supplier shall provide orientation/training on the use and maintenance of the Patient Transport Vehicle on a schedule to be agreed upon by Procuring Entity and the winning bidder. 2. The supplier shall submit/provide the following to the end user: <ul style="list-style-type: none"> a. operator’s manual in English language for the vehicle, Stretcher and Oxygen Cylinder; b. Warranty Certificate for not less than three (3) years on parts and no less than five (5) on services for the Patient Transport Vehicle. The manufacturer/dealer shall either repair or replace any item or part in the Patient Transport Vehicle that is found to be defective in material or in workmanship under normal use. The warranty period shall commence from the date of acceptance by the end-user after testing and commissioning. The warranty certificate shall include the following: <ul style="list-style-type: none"> <i>b.1 Free preventive maintenance for the vehicle every 10,000 km up to 30,000km as indicated in the vehicle odometer. The free preventive maintenance shall be comprised of free change oil, brake check-up cleaning, and battery check-up.</i> b.2 The warranty and preventive maintenance shall be applicable to any vehicle brand dealership. b.3. That if the Patient Transport Vehicle is unable to return to the service center during the warranty period, the manufacture/dealer shall provide mechanics and/or technicians that can perform on-site service and maintenance, provided that the end user will shoulder the travel expenses. c. At least three (3) years validity Land Transportation Office (LTO) registration with red plate d, Third Party Liability (TPL) vehicle insurance for one (1) year and comprehensive GSIS vehicle insurance for one (1) year. <p>DELIVERY</p> <ol style="list-style-type: none"> 1. The delivery of the Patient Transport Vehicle shall be completed within 120 calendar days upon issuance of the Notice to Proceed (NTP) 2. Upon delivery, each Patient Transport Vehicle shall undergo preliminary physical inspection by the Inspection Team of the Procuring Entity to ascertain the physical condition and acceptability of the units. The Patient Transport Vehicle accessories and peripherals must be functioning and must 	

