

#### Republic of the Philippines Department of Health

## METRO MANILA CENTER FOR HEALTH DEVELOPMENT



#### SUPPLEMENTAL/ BID BULLETIN NO. 1

### IB2025 – 008E PROCUREMENT OF 1 UNIT AUTOCLAVE MACHINE (HEAVY DUTY) (SHORT OF AWARD

This Supplemental/Bid Bulletin No. 1 is being issued to revise provisions/specifications in the Bidding Documents for a forecited project:

Query during Pre-bidding C	onference:						
Technical Specification	Query	Response of the End User Unit					
No changes stipulated in the Technical Specifications							
The Bidder's SLCC as indicated in <b>ITB</b> Clause 5.3 should have been completed within five (5) years prior to the deadline for the submission and receipt of bids.							
The Bidder must have completed a two or more contract that is similar to this Project							
Use the MMCHD Template fo which is included below.	r Omnibus Sworn Statement Revise	ed with Secretary Certificate,					

Bidders are advised to use the following attached forms and submit them together with all required documents for the submission of bids on the 17<sup>th</sup> day of December 2024, 9:00 AM, Amphitheater.

This Supplemental/Bid Bulletin No. 1 shall be integral to the Bidding Documents. All other provisions indicated in the bidding documents not affected by this Supplemental/Bid Bulletin No. 1 shall remain in effect.

For guidance and information of all concerned.

Issued this 10<sup>th</sup> day of December 2024 in MMCHD

Approved by:

Licensing Officer V / BAC Chairperson

# Republic of the Philippines Department of Health Metro Manila Center for Health Development

Item No. 1 AUTOCLAVE MACHINE (HEAVY Duty) Qty./Unit   1Unit   Name of Manufacturer: Country of Origin   Brand: Model: (if applicable)   ARC: 1,300,000.00   Technical Specifications: Horizontal Chamber of large capacity suited for: Starlizing gauze   - Origin   - Sterilizing gauze   - Origin   - Sterilizing gauze   - Garments   - Surgical Instruments   - Chamber and door are made of thick stainless steel for most durable and long lasting service   - High pressure resistant stainless steel radial locking bars combine door handles   - Sasily replaceable silicon rubber door gasket   - Jacket Insulation: Manufacturer's standard   - Illuminated lamps indicate each stage of operating cycle   - With built-in:   - Steam generator electrically heated   - Separate pressure gauge of chamber and jacket   - Manually adjustable automatic pressure controller / regulator   - Safety valve and lower water level shut off device   - The package includes a stainless steel shelf   - Chamber Depth: at least 1000 mm   - Power Supply: 220V, 50/60   - Temperature Ranges: up to 2.25 Kg/cm²   - Drying Time Adjustment: 10-60 mins   - Sternilizing fime (adjustment): 40-60 mins   - Chamber Volume: At least 280 L or better   - Dimensions: Manufacturer's Standard   - Net Weight: Manufacturer's Standard   - Net Weight: Manufacturer's Standard   - Net Weight: Manufacturer's Standard   - With Biological incubator auto reader   - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)   - Monitor: at least 7" TFT Touch Screen   - Built-in code scanner for the biological indicator   - With integrated indication light   - Plasma reading time: ≤ 20 mins   - Steam reading time: ≤ 20 mins   - Steam reading time: ≤ 20 mins   - LTFS reading time: ≤ 1 hr   - Ethylene Oxide readi	Department of Health Metro Manila Center for Health Development							
Item No. 1 AUTOCLAVE MACHINE (HEAVY Duty) Qty./Unit Dunit Country of Origin  Brand: Model: (if applicable)  ABC: 1,300,000.00  PURCHASER'S SPECIFICATION  Technical Specifications:  + Horizontal Chamber of large capacity suited for:  - Stertilizing gauze  - Dressing gauze  - Dressing gauze  - Garments  - Chamber and door are made of thick stainless steel for most durable and long lasting service  - High pressure resistant stainless steel radial locking bars combine door handles  - Easily replaceable silicon rubber door gasket  - Jacket Insulation: Manufacturer's standard  - Illuminated lamps indicate each stage of operating cycle  - With built-in:  - Steam generator electrically heated  - Separate pressure gauge of chamber and jacket  - Manually adjustable automatic pressure controller / regulator  - Safety valve and lower water level shut off device  - The package includes a stainless steel shelf  - Chamber Depth: at least 1000 mm  - Power Supply: 220V, 50/60  - Temperature Ranges: up to 134°C  - Pressure Ranges: up to 2.25 Kg/cm²  - Drying Time Adjustment: 10-60 mins  - Sterilizing Time (adjustment): 40-60 mins  - Chamber Volume: At least 280 L or better  - Dimensions: Manufacturer's Standard  - Net Weight: Manufacturer's Standard  - Net Weight: Manufacturer's Standard  - Net Weight: Manufacturer's Standard  - With Biological incubator autor reader  - 4 in 1 (can read Plasma, Steam, LTTS, and Ethylene Oxide)  - Monitor: at least 7" TFT Touch Screen  - Built-in code scanner for the biological indicator  - With integrated indication light  - Plasma reading time: ≤ 20 mins  - LTFS reading time: ≤ 1 hr  - Ethylene Oxide reading time: ≤ 4 hrs  - Incubation Slots: at least 8 or better			-	icht.				
Name of Manufacturer:  Brand:  Model: (if applicable)  Model: (if applicable)  PURCHASER'S SPECIFICATION  Technical Specifications:  - Horizontal Chamber of large capacity suited for:  - Sterilizing gauze  - Dressing gauze  - Dressing gauze  - Carments  - Surgical Instruments  - Chamber and door are made of thick stainless steel for most durable and long lasting service  - High pressure resistant stainless steel radial locking bars combine door handles  - Easily replaceable silicon rubber door gasket  - High pressure resistant stainless steel radial locking bars combine door handles  - Easily replaceable silicon rubber door gasket  - With built-in:  - Steam generator electrically heated  - Separate pressure gauge of chamber and jacket  - Manually adjustable automatic pressure controller / regulator  - Safety valve and lower water level shut off device  - The package includes a stainless steel shelf  - Chamber Depth: at least 1000 mm  - Power Supply: 220V, 50/60  - Temperature Ranges: up to 134°C  - Pressure Ranges: up to 134°C  - Pressure Ranges: up to 14°C  - Pressure Ranges: up to 14°C  - Pressure Ranges: up to 14°C  - Pressure Ranges: up to 2.25 Kg/cm²  - Drying Time Adjustment: 10-60 mins  - Sterilizing Time (adjustment): 40-60 mins  - Sterilizing Time (adjustment): 40-60 mins  - Chamber Volume: At least 280 L or better  - Dilmensions: Manufacturer's Standard  - Net Weight: Manufacturer's Standard  - Net Weight: Manufacturer's Standard  - With Biological incubator auto reader  - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)  - Monitor: at least 7"TFT Touch Screen  - Built-in code scanner for the biological indicator  - With integrated indication light  - Plasma reading time: ≤ 20 mins  - Steam reading time: ≤ 20 mins  - Steam reading time: ≤ 20 mins  - LTFS reading time of the screen  - Ethylene Oxide reading time: ≤ 4 hrs  - Incubation Slots: at least 8 or better				1				
Brand:  ABC: 1,300,000.00  PURCHASER'S SPECIFICATION  Technical Specifications:  Horizontal Chamber of large capacity suited for:  Sterilizing gauze  Oressing gauze  Garments  Chamber and door are made of thick stainless steel for most durable and long lasting service  High pressure resistant stainless steel radial locking bars combine door handles  Easily replaceable silicon rubber door gasket  Jacket Insulation: Manufacturer's standard  Illuminated lamps indicate each stage of operating cycle  With built-in:  Steam generator electrically heated  Separate pressure gauge of chamber and jacket  Manually adjustable automatic pressure controller / regulator  Safety valve and lower water level shut off device  The package includes a stainless steel shelf  Chamber Depth: at least 1000 mm  Power Supply: 220V, 50/60  Temperature Ranges: up to 134°C  Pressure Ranges: up to 134°C  Pressure Ranges: up to 12.25 Kg/cm²  Drying Time Adjustment: 10-60 mins  Sterilizing Time (adjustment): 40-60 mins  Sterilizing T	Item No. 1	AUTOCLAVE MACHINE (HEAVY Duty)	Qty./Unit	1Unit				
BEC: 1,300,000.00  PURCHASER'S SPECIFICATION  Technical Specifications:  Horizontal Chamber of large capacity suited for:  Sterilizing gauze  Oursesing gauze  Carments  Chamber and door are made of thick stainless steel for most durable and long lasting service  High pressure resistant stainless steel radial locking bars combine door handles  Easily replaceable silicon rubber door gasket  Jacket Insulation: Manufacturer's standard  Illuminated lamps indicate each stage of operating cycle  With built-in: Steam generator electrically heated Separate pressure gauge of chamber and jacket  Manually adjustable automatic pressure controller / regulator Safety valve and lower water level shut off device  The package includes a stainless steel shelf Chamber Depth: at least 1000 mm  Power Supply: 220V, 50/60  Temperature Ranges: up to 134°C  Pressure Ranges: up to 2.25 Kg/cm²  Drying Time Adjustment: 10-60 mins Sterilizing Time (adjustment): 40-60 mins Sterilizing Time (adjustment): 40-60 mins  Stember Volume: At least 280 L or better  Dimensions: Manufacturer's Standard  Net Weight: Manufacturer's Standard  With Biological incubator auto reader  4 in 1 (can read Plasma, Steam, LTFs, and Ethylene Oxide) Monitor: at least 7" FTT Touch Screen  Built-in code scanner for the biological indicator  With integrated indication light Plasma reading time: ≤ 20 mins Steam reading time: ≤ 20 mins Steam reading time: ≤ 20 mins LTFS reading time: ≤ 1 hr Ethylene Oxide reading time: ≤ 4 hrs Incubation Slots: at least 8 or better	Name of Manuf	acturer:		Country of Origin				
PURCHASER'S SPECIFICATION  Technical Specifications:  Horizontal Chamber of large capacity suited for:  Sterilizing gauze  Dressing gauze  Garments  Sungical Instruments  Chamber and door are made of thick stainless steel for most durable and long lasting service  High pressure resistant stainless steel radial locking bars combine door handles  Easily replaceable silicon rubber door gasket  Jacket Insulation: Manufacturer's standard  Illuminated lamps indicate each stage of operating cycle  With built-in:  Steam generator electrically heated  Separate pressure gauge of chamber and jacket  Manually adjustable automatic pressure controller / regulator  Safety valve and lower water level shut off device  The package includes a stainless steel shelf  Chamber Depth: at least 1000 mm  Power Supply: 220V, 50/60  Temperature Ranges: up to 134°C  Pressure Ranges: up to 2.25 Kg/cm²  Drying Time Adjustment: 10-60 mins  Sterilizing Time (adjustment): 40-60 mins  Sterilizing Time (adjustment): 40-60 mins  Sterilizing Time (adjustment): 40-60 mins  Othamber Volume: At least 280 L or better  Dimensions: Manufacturer's Standard  Net Weight: Manufacturer's Standard  Net Try Try Touch Screen  Built-in code scanner for the biological indicator  With integrated indication light  Plasma reading time: ≤ 20 mins  Sterm reading time: ≤ 1 hr  Ethylene Oxide reading time: ≤ 4 hrs  Incubation Slots: at least 8 or better	Brand:			Model: (if applicable)				
Technical Specifications:	ABC: <b>1,300,00</b> (	0.00						
<ul> <li>Horizontal Chamber of large capacity suited for: <ul> <li>Sterilizing gauze</li> <li>Oressing gauze</li> <li>Garments</li> <li>Chamber and door are made of thick stainless steel for most durable and long lasting service</li> <li>High pressure resistant stainless steel radial locking bars combine door handles</li> <li>Easily replaceable silicon rubber door gasket</li> <li>Jacket Insulation: Manufacturer's standard</li> <li>Illuminated lamps indicate each stage of operating cycle</li> <li>With built-in: <ul> <li>Steam generator electrically heated</li> <li>Separate pressure gauge of chamber and jacket</li> <li>Manually adjustable automatic pressure controller / regulator</li> <li>Safety valve and lower water level shut off device</li> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>ITFS reading time: ≤ 20 mins</li> <li>ITFS reading time: ≤ 20 mins</li> <li>ITFS reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> </li> <li>REQUIREMENTS, if awarded the contract</li> </ul></li></ul>				STATEMENT OF COMPLIANCE				
- Sterilizing gauze - Dressing gauze - Garments - Surgical Instruments - Chamber and door are made of thick stainless steel for most durable and long lasting service - High pressure resistant stainless steel radial locking bars combine door handles - Easily replaceable silicon rubber door gasket - Jacket Insulation: Manufacturer's standard - Illuminated lamps indicate each stage of operating cycle - With built-in: - Steam generator electrically heated - Separate pressure gauge of chamber and jacket - Manually adjustable automatic pressure controller / regulator - Safety valve and lower water level shut off device - The package includes a stainless steel shelf - Chamber Depth: at least 1000 mm - Power Supply: 220V, 50/60 - Temperature Ranges: up to 134°C - Pressure Ranges: up to 2.25 Kg/cm² - Drying Time Adjustment: 10-60 mins - Sterilizing Time (adjustment): 40-60 mins - Sterilizing Time (adjustment): 40-60 mins - Chamber Volume: At least 280 L or better - Dimensions: Manufacturer's Standard - Net Weight: Manufacturer's Standard - With Biological incubator auto reader - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasmar reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 20 mins - LTFS reading time: ≤ 20 mins - ITFS reading time: ≤ 20 mins - ITFS reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better								
- Dressing gauze - Garments - Surgical Instruments - Chamber and door are made of thick stainless steel for most durable and long lasting service - High pressure resistant stainless steel radial locking bars combine door handles - Easily replaceable silicon rubber door gasket - Jacket Insulation: Manufacturer's standard - Illuminated lamps indicate each stage of operating cycle - With built-in: - Steam generator electrically heated - Separate pressure gauge of chamber and jacket - Manually adjustable automatic pressure controller / regulator - Safety valve and lower water level shut off device - The package includes a stainless steel shelf - Chamber Depth: at least 1000 mm - Power Supply: 220V, 50/60 - Temperature Ranges: up to 134°C - Pressure Ranges: up to 2.25 Kg/cm² - Drying Time Adjustment: 10-60 mins - Sterilizing Time (adjustment): 40-60 mins - Sterilizing Time (adjustment): 40-60 mins - Chamber Volume: At least 280 L or better - Dimensions: Manufacturer's Standard - Net Weight: Manufacturer's Standard - Net Weight: Manufacturer's Standard - With Biological incubator auto reader - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - Steam reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better								
- Garments - Surgical Instruments  • Chamber and door are made of thick stainless steel for most durable and long lasting service  • High pressure resistant stainless steel radial locking bars combine door handles  • Easily replaceable silicon rubber door gasket  • Jacket Insulation: Manufacturer's standard  • Illuminated lamps indicate each stage of operating cycle  • With built-in:  • Steam generator electrically heated  • Separate pressure gauge of chamber and jacket  • Manually adjustable automatic pressure controller / regulator  • Safety valve and lower water level shut off device  • The package includes a stainless steel shelf  • Chamber Depth: at least 1000 mm  • Power Supply: 220V, 50/60  • Temperature Ranges: up to 134°C  • Pressure Ranges: up to 2.25 Kg/cm²  • Drying Time Adjustment: 10-60 mins  • Sterilizing Time (adjustment): 40-60 mins  • Sterilizing Time (adjustment): 40-60 mins  • Chamber Volume: At least 280 L or better  • Dimensions: Manufacturer's Standard  • With Biological incubator auto reader  • 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)  • Monitor: at least 7" TFT Touch Screen  • Built-in code scanner for the biological indicator  • With integrated indication light  • Plasma reading time: ≤ 20 mins  • Steam reading time: ≤ 20 mins  • Steam reading time: ≤ 1 hr  • Ethylene Oxide reading time: ≤ 4 hrs  • Incubation Slots: at least 8 or better	_							
- Surgical Instruments  • Chamber and door are made of thick stainless steel for most durable and long lasting service  • High pressure resistant stainless steel radial locking bars combine door handles  • Easily replaceable silicon rubber door gasket  • Jacket Insulation: Manufacturer's standard  • Illuminated lamps indicate each stage of operating cycle  • With built-in:  • Steam generator electrically heated  • Separate pressure gauge of chamber and jacket  • Manually adjustable automatic pressure controller / regulator  • Safety valve and lower water level shut off device  • The package includes a stainless steel shelf  • Chamber Depth: at least 1000 mm  • Power Supply: 220V, 50/60  • Temperature Ranges: up to 134°C  • Pressure Ranges: up to 2.25 Kg/cm²  • Drying Time Adjustment: 10-60 mins  • Sterilizing Time (adjustment): 40-60 mins  • Chamber Volume: At least 280 L or better  • Dimensions: Manufacturer's Standard  • Net Weight: Manufacturer's Standard  • Net Weight: Manufacturer's Standard  • With Biological incubator auto reader  • 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)  • Monitor: at least 7" TFT Touch Screen  • Built-in code scanner for the biological indicator  • With integrated indication light  • Plasma reading time: ≤ 20 mins  • Steam reading time: ≤ 20 mins  • Steam reading time: ≤ 1 hr  • Ethylene Oxide reading time: ≤ 4 hrs  • Incubation Slots: at least 8 or better		auze						
• Chamber and door are made of thick stainless steel for most durable and long lasting service  • High pressure resistant stainless steel radial locking bars combine door handles  • Easily replaceable silicon rubber door gasket  • Jacket Insulation: Manufacturer's standard  • Illuminated lamps indicate each stage of operating cycle  • With built-in:  • Steam generator electrically heated  • Separate pressure gauge of chamber and jacket  • Manually adjustable automatic pressure controller / regulator  • Safety valve and lower water level shut off device  • The package includes a stainless steel shelf  • Chamber Depth: at least 1000 mm  • Power Supply: 220V, 50/60  • Temperature Ranges: up to 134°C  • Pressure Ranges: up to 2.25 Kg/cm²  • Drying Time Adjustment: 10-60 mins  • Sterilizing Time (adjustment): 40-60 mins  • Sterilizing Time (adjustment): 40-60 mins  • Chamber Volume: At least 280 L or better  • Dimensions: Manufacturer's Standard  • Net Weight: Manufacturer's Standard  • With Biological incubator auto reader  • 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)  • Monitor: at least 7" TFT Touch Screen  • Built-in code scanner for the biological indicator  • With integrated indication light  • Plasma reading time: ≤ 20 mins  • Steam reading time: ≤ 20 mins  • Steam reading time: ≤ 1 hr  • Ethylene Oxide reading time: ≤ 4 hrs  • Incubation Slots: at least 8 or better		atrumenta						
In the pressure resistant stainless steel radial locking bars combine door handles   Easily replaceable silicon rubber door gasket   Jacket Insulation: Manufacturer's standard   Illuminated lamps indicate each stage of operating cycle   With built-in:   Steam generator electrically heated   Separate pressure gauge of chamber and jacket   Manually adjustable automatic pressure controller / regulator   Safety valve and lower water level shut off device   The package includes a stainless steel shelf   Chamber Depth: at least 1000 mm   Power Supply: 220V, 50/60   Temperature Ranges: up to 134°C   Pressure Ranges: up to 2.25 Kg/cm²   Drying Time Adjustment: 10-60 mins   Sterilizing Time (adjustment): 40-60 mins   Chamber Volume: At least 280 L or better   Dimensions: Manufacturer's Standard   Net Weight: Manufacturer's Standard   With Biological incubator auto reader   4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)   Monitor: at least 7" TFT Touch Screen   Built-in code scanner for the biological indicator   With integrated indication light   Plasma reading time: ≤ 20 mins   Steam reading time: ≤ 20 mins   Steam reading time: ≤ 1 hr   Ethylene Oxide reading time: ≤ 4 hrs   Incubation Slots: at least 8 or better			t durable and					
<ul> <li>High pressure resistant stainless steel radial locking bars combine door handles</li> <li>Easily replaceable silicon rubber door gasket</li> <li>Jacket Insulation: Manufacturer's standard</li> <li>Illuminated lamps indicate each stage of operating cycle</li> <li>With built-in:         <ul> <li>Steam generator electrically heated</li> <li>Separate pressure gauge of chamber and jacket</li> <li>Manually adjustable automatic pressure controller / regulator</li> <li>Safety valve and lower water level shut off device</li> </ul> </li> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> <li>REQUIREMENTS, if awarded the contract</li>			t dui able allu					
<ul> <li>Easily replaceable silicon rubber door gasket</li> <li>Jacket Insulation: Manufacturer's standard</li> <li>Illuminated lamps indicate each stage of operating cycle</li> <li>With built-in: <ul> <li>Steam generator electrically heated</li> <li>Separate pressure gauge of chamber and jacket</li> <li>Manually adjustable automatic pressure controller / regulator</li> <li>Safety valve and lower water level shut off device</li> </ul> </li> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> <li>REQUIREMENTS, if awarded the contract</li>			omhine door					
<ul> <li>Easily replaceable silicon rubber door gasket</li> <li>Jacket Insulation: Manufacturer's standard</li> <li>Illuminated lamps indicate each stage of operating cycle</li> <li>With built-in: <ul> <li>Steam generator electrically heated</li> <li>Separate pressure gauge of chamber and jacket</li> <li>Manually adjustable automatic pressure controller / regulator</li> <li>Safety valve and lower water level shut off device</li> </ul> </li> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> <li>REQUIREMENTS, if awarded the contract</li>	~ .	resistant stanness steer radial locking bars (	ombine door					
• Jacket Insulation: Manufacturer's standard • Illuminated lamps indicate each stage of operating cycle • With built-in: - Steam generator electrically heated - Separate pressure gauge of chamber and jacket - Manually adjustable automatic pressure controller / regulator - Safety valve and lower water level shut off device • The package includes a stainless steel shelf • Chamber Depth: at least 1000 mm • Power Supply: 220V, 50/60 • Temperature Ranges: up to 134°C • Pressure Ranges: up to 2.25 Kg/cm² • Drying Time Adjustment: 10-60 mins • Sterilizing Time (adjustment): 40-60 mins • Sterilizing Time (adjustment): 40-60 mins • Chamber Volume: At least 280 L or better • Dimensions: Manufacturer's Standard • Net Weight: Manufacturer's Standard • Net Weight: Manufacturer's Standard • With Biological incubator auto reader - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better		able silicon rubber door gasket						
<ul> <li>• Illuminated lamps indicate each stage of operating cycle</li> <li>• With built-in:</li> <li>- Steam generator electrically heated</li> <li>- Separate pressure gauge of chamber and jacket</li> <li>- Manually adjustable automatic pressure controller / regulator</li> <li>- Safety valve and lower water level shut off device</li> <li>• The package includes a stainless steel shelf</li> <li>• Chamber Depth: at least 1000 mm</li> <li>• Power Supply: 220V, 50/60</li> <li>• Temperature Ranges: up to 134°C</li> <li>• Pressure Ranges: up to 2.25 Kg/cm²</li> <li>• Drying Time Adjustment: 10-60 mins</li> <li>• Sterilizing Time (adjustment): 40-60 mins</li> <li>• Chamber Volume: At least 280 L or better</li> <li>• Dimensions: Manufacturer's Standard</li> <li>• Net Weight: Manufacturer's Standard</li> <li>• With Biological incubator auto reader</li> <li>- 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>• Monitor: at least 7" TFT Touch Screen</li> <li>- Built-in code scanner for the biological indicator</li> <li>- With integrated indication light</li> <li>- Plasma reading time: ≤ 20 mins</li> <li>- Steam reading time: ≤ 20 mins</li> <li>- LTFS reading time: ≤ 20 mins</li> <li>- LTFS reading time: ≤ 1 hr</li> <li>- Ethylene Oxide reading time: ≤ 4 hrs</li> <li>- Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract								
<ul> <li>With built-in:     <ul> <li>Steam generator electrically heated</li> <li>Separate pressure gauge of chamber and jacket</li> <li>Manually adjustable automatic pressure controller / regulator</li> <li>Safety valve and lower water level shut off device</li> </ul> </li> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> <li>REQUIREMENTS, if awarded the contract</li>								
- Separate pressure gauge of chamber and jacket - Manually adjustable automatic pressure controller / regulator - Safety valve and lower water level shut off device  The package includes a stainless steel shelf - Chamber Depth: at least 1000 mm  Power Supply: 220V, 50/60  Temperature Ranges: up to 134°C  Pressure Ranges: up to 2.25 Kg/cm²  Drying Time Adjustment: 10-60 mins - Sterilizing Time (adjustment): 40-60 mins - Chamber Volume: At least 280 L or better  Dimensions: Manufacturer's Standard - Net Weight: Manufacturer's Standard - With Biological incubator auto reader - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better								
- Manually adjustable automatic pressure controller / regulator - Safety valve and lower water level shut off device  • The package includes a stainless steel shelf • Chamber Depth: at least 1000 mm • Power Supply: 220V, 50/60 • Temperature Ranges: up to 134°C • Pressure Ranges: up to 2.25 Kg/cm² • Drying Time Adjustment: 10-60 mins • Sterilizing Time (adjustment): 40-60 mins • Chamber Volume: At least 280 L or better • Dimensions: Manufacturer's Standard • Net Weight: Manufacturer's Standard • With Biological incubator auto reader - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better	- Steam gen	erator electrically heated						
- Safety valve and lower water level shut off device  • The package includes a stainless steel shelf • Chamber Depth: at least 1000 mm • Power Supply: 220V, 50/60 • Temperature Ranges: up to 134°C • Pressure Ranges: up to 2.25 Kg/cm² • Drying Time Adjustment: 10-60 mins • Sterilizing Time (adjustment): 40-60 mins • Chamber Volume: At least 280 L or better • Dimensions: Manufacturer's Standard • Net Weight: Manufacturer's Standard • With Biological incubator auto reader • 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) • Monitor: at least 7" TFT Touch Screen • Built-in code scanner for the biological indicator • With integrated indication light • Plasma reading time: ≤ 20 mins • Steam reading time: ≤ 20 mins • LTFS reading time: ≤ 1 hr • Ethylene Oxide reading time: ≤ 4 hrs • Incubation Slots: at least 8 or better		,						
<ul> <li>The package includes a stainless steel shelf</li> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract			ulator					
<ul> <li>Chamber Depth: at least 1000 mm</li> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract	_							
<ul> <li>Power Supply: 220V, 50/60</li> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader <ul> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> </li> </ul> REQUIREMENTS, if awarded the contract								
<ul> <li>Temperature Ranges: up to 134°C</li> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract								
<ul> <li>Pressure Ranges: up to 2.25 Kg/cm²</li> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader <ul> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> </li> </ul>								
<ul> <li>Drying Time Adjustment: 10-60 mins</li> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader <ul> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> </li> </ul> REQUIREMENTS, if awarded the contract	-							
<ul> <li>Sterilizing Time (adjustment): 40-60 mins</li> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader <ul> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> </li> <li>REQUIREMENTS, if awarded the contract</li> </ul>	_	= -						
<ul> <li>Chamber Volume: At least 280 L or better</li> <li>Dimensions: Manufacturer's Standard</li> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader  - 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)  - Monitor: at least 7" TFT Touch Screen  - Built-in code scanner for the biological indicator  - With integrated indication light  - Plasma reading time: ≤ 20 mins  - Steam reading time: ≤ 20 mins  - LTFS reading time: ≤ 1 hr  - Ethylene Oxide reading time: ≤ 4 hrs  - Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract								
<ul> <li>Net Weight: Manufacturer's Standard</li> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract		• ,						
<ul> <li>With Biological incubator auto reader</li> <li>4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide)</li> <li>Monitor: at least 7" TFT Touch Screen</li> <li>Built-in code scanner for the biological indicator</li> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract	• Dimensions: N	Aanufacturer's Standard						
- 4 in 1 (can read Plasma, Steam, LTFS, and Ethylene Oxide) - Monitor: at least 7" TFT Touch Screen - Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better	• Net Weight: M	Ianufacturer's Standard						
<ul> <li>- Monitor: at least 7" TFT Touch Screen</li> <li>- Built-in code scanner for the biological indicator</li> <li>- With integrated indication light</li> <li>- Plasma reading time: ≤ 20 mins</li> <li>- Steam reading time: ≤ 20 mins</li> <li>- LTFS reading time: ≤ 1 hr</li> <li>- Ethylene Oxide reading time: ≤ 4 hrs</li> <li>- Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract			_					
- Built-in code scanner for the biological indicator - With integrated indication light - Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract			<del>e</del> )					
<ul> <li>With integrated indication light</li> <li>Plasma reading time: ≤ 20 mins</li> <li>Steam reading time: ≤ 20 mins</li> <li>LTFS reading time: ≤ 1 hr</li> <li>Ethylene Oxide reading time: ≤ 4 hrs</li> <li>Incubation Slots: at least 8 or better</li> </ul> REQUIREMENTS, if awarded the contract								
- Plasma reading time: ≤ 20 mins - Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract		<del>-</del>						
- Steam reading time: ≤ 20 mins - LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract	_							
- LTFS reading time: ≤ 1 hr - Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract								
- Ethylene Oxide reading time: ≤ 4 hrs - Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract								
- Incubation Slots: at least 8 or better  REQUIREMENTS, if awarded the contract		•						
· ·	_							
· ·	REQUIREMENT	S, if awarded the contract						
1. Completion Period: The delivery, installation, testing and	-							
commissioning of the equipment and its accessories, including the training	_		g the training					

of end-users and maintenance staff must be completed within 90 calendar days upon receipt of Notice to Proceed.

- 2. Testing: Prior to acceptance, the end user shall conduct a physical inspection and functionality test. The equipment must be functioning and must have no physical damage and defect.
- 3. Training: The supplier shall provide a training on the proper use and maintenance of the equipment to the end-users and to the hospital maintenance staff within 3 days upon delivery of the equipment. .
- 4. Warranty:
- a) Warranty certificate for two (2) years on parts and service. The supplier shall either repair or replace any item or part in the equipment that is found to be defective in material or workmanship under normal use. The warranty period shall commence from the date of acceptance by the end-user after testing and commissioning.
- b) Preventive maintenance at least every six (6) months or according to the manufacturer's recommendations;
- c) Corrective maintenance within five (5) calendar days upon notification from the end-user regarding equipment breakdown/defects.
- d) The number of days where the equipment is unusable due to equipment defects/faults shall be added to the warranty period.
- e) The supplier shall specify post-warranty comprehensive preventive maintenance costs including list and prices of major spare parts of the equipment for three (3) years after the warranty period.
- 5. Notarized undertaking that the supplier shall conduct the necessary corrective maintenance within five (5) calendar days upon notification of the equipment breakdown from the end-user. The undertaking shall include a statement that the number of days where the equipment is unusable due to defective material or workmanship, shall be added to the warranty period.
- 6. Manuals: The supplier must provide the end-user one (1) hard and one (1) soft copy of the following:
  - a) Service manual in English language
  - b) Operation manual in English language
- 7. With "DOH-MMCHD HFEP (Government Property not for sale)" sticker in each unit.

Source of Fund: NEP 2025 (Short of Award)

Recipients:

Ospital ng Paranaque II - 1 unit

For Sole Proprietorships)
(use Bidder's Official Letterhead)

#### SPECIAL POWER OF ATTORNEY

I,, Fili	pino, of legal age, doing business under the trade name and style of
	nized and existing under Philippine laws, with principal office address at
here	by name, constitute, and appoint (Name
and all acts necessary to participat the Bid Securing Declaration and/o Metro Manila Center for Health De	zed representative and attorney-in-fact to do, execute, and perform any e, submit bids, sign and execute documents and instruments, including or to represent me in any and all bidding proceedings conducted by the evelopment for the Bid Project
(Indicate Bid Project Title and No.)	):
necessary or proper to render effec lawfully do if personally present, and do with full power of substitution a or cause to be done by virtue hereo IN WITNESS WHEREOF, I have	hereunto affixed my signature on this day of
, 20 at	<del>.</del>
	Affiant/Principal
Attorney-in-Fact	
Signed in the Presence of:	
Witness	Witness

NOTE: PLS. USE THIS FORM ONLY IF THE REGISTERED PROPRIETOR OPTS TO

AUTHORIZE ANOTHER PERSON TO REPRESENT HER/HIM TO DO, EXECUTE, AND PERFORM ANY AND ALL ACTS NECESSARY IN ORDER TO PARTICIPATE, SUBMIT BIDS, SIGN AND EXECUTE DOCUMENTS PERTAINING TO THE BID PROJECT.)

# $For\ FORMED\ Joint\ Venture\ \hbox{-}\ Incorporated)$

(use Bidder's Official Letterhead) REPUBLIC OF THE PHILIPPINES) ) S.S.

## SECRETARY'S CERTIFICATE

(Name of the Corporate Secretary), the Corporate Secretary of the
(Name of the Corporation), a corporation duly organized and existing under
and by virtue of the laws of the Philippines with principal office at
Address of the Corporation) (the "Corporation"), after having been duly sworn according to law, does hereby certify that at the meeting of the Board of
Directors of the said Corporation duly convened and held on (Date of the meeting)
at (Place of the meeting) at which a quorum was present and
acted throughout, the following resolutions were unanimously approved and adopted through Board
Resolution No (Indicate Board Resolution No.), Series of 20:
"RESOLVED, that (Name of the Joint Venture) is authorized to
participate in the bidding of (Project ID-No.)
of the Metro Manila Center for Health Development ("MMCHD" or
the "Procuring Entity"); and that in connection with the said bidding, the following is/are hereby
appointed and designated as the duly authorized representative/s of the JV, granted with full power
and authority to do, execute and perform any and all acts necessary and/or to represent the JV to
participate in the bidding of the above-mentioned project which includes to sign for and in behalf of
the JV all bid documents, submit the bid, and to sign contracts, agreements, instruments, statements,
reports, and other documents pertaining to the bidding including the ensuing contract with MMCHD
and all other documents, as may be required:
Name Position
<del></del>
·
acting in this manner1:
1. Any one (1) of the above signatories
2 All of the above signatories
3. Any (state the number) of the above signatories (in case the Board opts to have joint
signing from designated representatives, i.e. any 2 jointly signing out of 4)
RESOLVED FURTHER THAT, (Name of the JV):
(1) the Submits itself to the jurisdiction of the Philippine government and waives its right to question
the jurisdiction of the Philippine courts; and
(2) Shall neither seek nor obtain writs of injunction or prohibition or restraining order against the
MMCHD or any other agency in connection with this project to prevent and restrain the bidding
procedures related thereto, the negotiating of the award of a contract to a successful bidder, and the
carrying out of the awarded contract.
RESOLVED FINALLY, that the foregoing authorities shall remain in full force and effect and
binding on the Corporation until notice in writing is received by MMCHD, revoking, amending, or
otherwise modifying the same."
The undersigned further certifies that the foregoing resolutions have not been revoked, amended, or
otherwise modified, and remain valid and subsisting.
The foregoing excerpts of the minutes of the Board meeting are true and correct and in accordance
with the corporate records under my custody and are consistent with the Articles of Incorporation and
By-laws of the Corporation.  IN WITNESS WHEREOF, I have hereunto affixed my signature on this day of, 20
at
Corporate Secretary
SUBSCRIBED AND SWORN to before me, this day of , 20 at ,
affiant exhibiting to me his/her Competent Evidence of Identity issued on
attract exhibiting to the his/her competent Evidence of identity issued on at
Doc. No

Spec

Page No		
Book No		
Series of		
and by virtue of at	rhead) PPINES)  SECRETARY'S CER'  (Name of the Corporation), a country of the laws of the laws of the law, does hereby certify the convened and held on (Place of the meeting resolutions were unanimous ender the Project and Project (CHD" or the "Procuring Englished (Place) of the meeting resolution is hereby authors of the Project and Project (CHD" or the "Procuring Englished (Place) or t	re Secretary), the Corporate Secretary of the proporation duly organized and existing under Philippines with principal office orporation) (the "Corporation"), after having at at the meeting of the Board of Directors of (Date of the meeting) at (s) at which a quorum was present and acted asly approved and adopted through Board also of 20: norized to participate in the bidding of at ID No.) of the Metro Manila Center For tity") and if awarded the project shall enter the following is/are hereby appointed and the Corporation, granted with full power and essary and/or to represent the Corporation to
		t which includes to sign for and in behalf of
		to sign contracts, agreements, instruments,
		e bidding including the ensuing contract with
MMCHD and all other docu	ments, as may be required:	
Name	Position	Specimen Signature
	natories	atories (in case the Board opts to have joint y signing out of 4)
<ul><li>(1) the Submits itself to the the jurisdiction of the Philip</li><li>(2) Shall neither seek nor of MMCHD or any other age</li></ul>	pine courts; and obtain writs of injunction or ncy in connection with this the negotiating of the award	(Name of the Corporation): government and waives its right to question prohibition or restraining order against the project to prevent and restrain the bidding of a contract to a successful bidder, and the

binding on the Corporation until notice in writing is received by MMCHD, revoking, amending, or otherwise modifying the same."

The undersigned further certifies that the foregoing resolutions have not been revoked, amended, or

RESOLVED FINALLY, that the foregoing authorities shall remain in full force and effect and

The undersigned further certifies that the foregoing resolutions have not been revoked, amended, or otherwise modified, and remain valid and subsisting.

The foregoing excerpts of the minutes of the Board meeting are true and correct and in accordance with the corporate records under my custody and are consistent with the Articles of Incorporation and By-laws of the Corporation.

IN WITNESS WHEREOF, I have hereunto affixed my signature on this day of at	f, 20
Corporate Secretary	
SUBSCRIBED AND SWORN to before me, this day of , 20 at affiant exhibiting to me his/her Competent Evidence of Identity at	, issued on
Doc. No Page No	
Book No Series of	

#### **Omnibus Sworn Statement (Revised)**

[shall be submitted with the Bid]

REPUBLIC OF THE PHILIPPINES )	
CITY/MUNICIPALITY OF) S.S.	

#### **AFFIDAVIT**

- I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:
- 1. [Select one, delete the other:]

[If a sole proprietorship:] I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];

[If a partnership, corporation, cooperative, or joint venture:] I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. [Select one, delete the other:]

[If a sole proprietorship:] As the owner and sole proprietor, or authorized representative of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached duly notarized Special Power of Attorney;

[If a partnership, corporation, cooperative, or joint venture:] I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];

- 3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;
- Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- 5. [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;
- 6. [Select one, delete the rest:]

[If a sole proprietorship:] The owner or sole proprietor is not related to the Head of the Procuring Entity, Procurement Agent if engaged, members of the Bids and Awards

Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, Procurement Agent if engaged, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, Procurement Agent if engaged, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards; and
- 8. [Name of Bidder] is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
  - a. Carefully examining all of the Bidding Documents;
  - Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract;
  - Making an estimate of the facilities available and needed for the contract to be bid, if any; and
  - Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or
  any form of consideration, pecuniary or otherwise, to any person or official, personnel or
  representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN	WITNESS	WHEREOF, I	have	hereunto	set	my	hand	this	_	day	of	,	20	at
		_, Philippines.												

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE] [Insert signatory's legal capacity] Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]