



Republic of the Philippines  
Department of Health  
**METRO MANILA CENTER FOR HEALTH DEVELOPMENT**

**SUPPLEMENTAL/ BID BULLETIN NO. 1**

**IB2024 – 044E  
PROCUREMENT OF RADIANT WARMER**

This Supplemental/Bid Bulletin No. 1 is being issued to revise provisions/specifications in the Bidding Documents for a forecited project:

1. Query during Pre-bidding Conference:

Technical Specifications	Query	Response of the End User Unit
Ceramic heater elements and golden reflectors.	Ceramic heater elements and golden reflectors or its equivalent	Ceramic heater elements and golden reflectors or <b><i>its equivalent</i></b>
With at least 10 heater level.	With at least 5 heater level or better	With at least 5 heater level <b><i>or better</i></b>
With at least 2 heater elements located at the Radiant warmer	With at least 1 heater elements located at the Radiant warmer or better	With at least 1 heater elements located at the Radiant warmer <b><i>or better</i></b>
Manual bed-tilt feature Head up position is 20 degrees.	Manual bed-tilt feature Head up position is 15 degrees or better	Manual bed-tilt feature Head up position is <b><i>15 degrees or better</i></b>
- Manual bed-tilt feature Head down position is 15 degrees	Manual bed-tilt feature Head down position is 12 degrees or better	Manual bed-tilt feature Head down position is <b><i>12 degrees or better</i></b>

**2. Completion Period:**

The delivery, installation, testing and commissioning of the equipment and its accessories, including the training of end-users and maintenance staff must be completed with 60 calendar days upon receipt of Notice to Proceed.

Bidders are advised to use the **following attached forms and submit them together with all required documents for the submission of bids on the 14<sup>th</sup> day of June 2024, 9:00 AM:**

This Supplemental/Bid Bulletin No. 1 shall be integral to the Bidding Documents. All other provisions indicated in the bidding documents not affected by this Supplemental/Bid Bulletin No. 1 shall remain in effect.

For guidance and information of all concerned.

Issued this 7<sup>th</sup> day of June 2024 in MMCHD

Approved by:

SGD.  
**JEREMIAS FRANCIS Y. CHAN, MD**  
Licensing Officer V / BAC Chairperson

### VII Technical Specification

Republic of the Philippines  
Department of Health  
Metro Manila Center for Health Development

#### TECHNICAL SPECIFICATIONS

<b>Item No. 1</b>	<b>PROCUREMENT OF RADIANT WARMER</b>	Qty./Unit	<b>5 UNITS</b>
Name of Manufacturer:		Country of Origin	
Brand:		Model: (if applicable)	
ABC: <b>1,250,000.00</b>			
PURCHASER'S SPECIFICATION		STATEMENT OF COMPLIANCE	
<p><b>TECHNICAL SPECIFICATIONS:</b></p> <ul style="list-style-type: none"> <li>• Movable Lamp mechanism that automatically focuses radiant warmth on the baby.</li> <li>• Lamp can be positioned on the overhead left or right side of the equipment.</li> <li>• Ceramic heater elements and golden reflectors <i>or its equivalent</i></li> <li>Radiant warmth with Two (2) brightness level Examination lamp features</li> <li>• With at <i>least 5 heater level or better</i></li> <li>• Radiant Warmer can be positioned from left to right direction for up to 90 degrees.</li> <li>• With at least <i>1 heater</i> elements located at the Radiant warmer <i>or better</i></li> <li>• With 30 watts day and 9 watts night examination light.</li> <li>• Radiant Power at Heat Level 3 between the bed and radiant warmer: 10mW/cm<sup>2</sup></li> <li>• Radiant Power at Heat Level 10 between the bed and radiant warmer: 30mW/cm<sup>2</sup></li> <li>• <b>Lamps (Work Light):</b> 30 Watts</li> <li>• <b>Lamps (Night Light):</b> 9 Watts</li> <li>• <b>Minimum clearance between top edge of Radiant warmer and Ceiling:</b> &gt;50cm</li> <li>• <b>Temperature</b> <ul style="list-style-type: none"> <li>- Capable of measuring baby's central or peripheral temperature.</li> <li>- Manual mode</li> <li>- Skin servo mode</li> <li>- With temperature measuring range of at least 15 degrees to 42 degrees</li> <li>- <b>Accuracy (Sensor):</b> ±0.1 degrees Celsius</li> <li>- <b>Setting Range:</b> 30 degrees Celsius to 38.5 degrees Celsius</li> </ul> </li> </ul>			



